

ANSI 150#

Cast Steel

SWING CHECK VALVES




Features

- Swing Type
- ANSI 150# Flange Connection
- Size: 1 1/2" - 6" (DN40 - DN150)
- Working Pressure: 150#
- Material: A216 WCB
- Applicable Medium: General oil, Gas & Water applications
- Temperature Range: -29°C to 425°C



ANSI 150# Cast Steel Flange End Swing Check Valves



Technical Specifications

1. Basic design and manufacture according to BS1868
2. End to end according to ASME B16.10
3. End connection complied with ASME B16.5
4. Inspection and tested according to API 598

Performance Specification Sheet			
Nominal pressure		150 #	
Test pressure	Shell Pressure test	3.0	MPa
	Sealing Pressure test	2.2	
	Air Pressure test	0.6	
Max working temperature		-29°C to 425°C	
Applicable Medium: General oil, gas & water			

Ordering Information

VL	-	CS	-	SC	-	F	-	150	-	24
I		II		III		IV		V		VI

I	Type of Item		
VL	Low Pressure Valves		

II	Material Grade		
S	SS316, CF8M	CI	Cast Iron
FS	Forged Steel	CS	Cast Steel
B	Brass		

III	Item		
GA	Gate Valve	B1	1 PC Ball Valve
GL	Globe Valve	B2	2 PC Ball Valve
YS	Y-Strainer	B3	3 PC Ball Valve
SC	Swing Check Valve	BL	3 Way Ball Valve L Port
VC	Vertical Check Valve	BT	3 Way Ball Valve T Port
WC	Wafer Check Valve	BMF	Male x Female Mini Ball Valve
DD	Dual Disk	BU	Butterfly Valve

IV	Connection Type		
SW	S/W	G	BSPP
BW	B/W	N	NPT
R	BSPT	F	Flange End
W	Wafer	L	Lug

V	Pressure		
200	200 PSI	2000	2000 PSI
300	300 PSI	150	ANSI 150# Flange Standard
600	600 PSI	10K	JIS 10K Flange Standard
800	800 PSI	PN16	PN 16 Flange Standard
1000	1000 PSI		

For Inch OD & Inch NB Sizes

IV	Size							
Size	1/8"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
Code	02	04	05	06	08	10	12	16
Size	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"
Code	20	24	32	40	48	64	80	96

VII	Coating		
(None)	No Additional Coating		
NI	Nickel Plating		

Material List

No.	Part Name	Material
1	Body	ASTM A216 WCB
2	Seat	ASTM A105 + F6
3	Disc	ASTM A216 WCB + F6
4	Hinge	ASTM A216 WCB
5	Hinge Pin	ASTM A276 410
6	Gasket	SS304 + GRAPHITE
7	Bonnet	ASTM A216 WCB
8	Bonnet Bolt Nut	ASTM A194 Gr.2H
9	Bonnet Bolt	ASTM A193 Gr.B7

Dimension List

NPS	Connection	Impa Code	Part No	D	D1	D2	d	H	L	Z-Ød	b	Weight (Kg)
1 1/2"	Flange-end	-	VL-CS-SC-F-150-24	127	98.5	73	38	115	165	4-Ø16	15	8.50
2"	Flange-end	-	VL-CS-SC-F-150-32	152	120.7	92	51	145	203	4-Ø19	16	13.80
2 1/2"	Flange-end	-	VL-CS-SC-F-150-40	177.8	139.7	104.7	64	150	216	4-Ø19	18	21.00
3"	Flange-end	-	VL-CS-SC-F-150-48	190.5	152.4	127	76	185	241	4-Ø19	19	27.00
4"	Flange-end	-	VL-CS-SC-F-150-64	229	190.5	157	102	215	292	8-Ø19	24	41.00
5"	Flange-end	-	VL-CS-SC-F-150-80	254	216	185.7	127	245	330	8-Ø22	24	55.00
6"	Flange-end	-	VL-CS-SC-F-150-96	279	241.3	216	152	260	356	8-Ø22	26	65.00

Part Number Reference

Impa Code	Part No	Description
-	VL-CS-SC-F-150-24	1 1/2" 150# CS FLANGE END SWING CHECK VALVE, METAL SEAT
-	VL-CS-SC-F-150-32	2" 150# CS FLANGE END SWING CHECK VALVE, METAL SEAT
-	VL-CS-SC-F-150-40	2 1/2" 150# CS FLANGE END SWING CHECK VALVE, METAL SEAT
-	VL-CS-SC-F-150-48	3" 150# CS FLANGE END SWING CHECK VALVE, METAL SEAT
-	VL-CS-SC-F-150-64	4" 150# CS FLANGE END SWING CHECK VALVE, METAL SEAT
-	VL-CS-SC-F-150-80	5" 150# CS FLANGE END SWING CHECK VALVE, METAL SEAT
-	VL-CS-SC-F-150-96	6" 150# CS FLANGE END SWING CHECK VALVE, METAL SEAT



AF HYDRO

Conditions of Use of Catalogue:

The information in the catalogue are not binding and in order to improve distribution, AF Hydro reserves the right to make any change including size and pressure ratings considered necessary at any time and without prior notice. According to the copyright and the civil law, any reproduction (also partial) of figures and texts of this catalogue by means of electronic, mechanical, photocopies, microfilms, recordings or other is forbidden without AF Hydro's authorization.